





T 1 STRIP FLOOR SPOTTED GUM 1 STRIP

QUICK-STEP READYFLOR TIMBER FLOORING

Quick-step pre-finished engineered floor single plank with an integrated no glue click system

SPECIES- Spotted Gum, Blackbutt, Jarrah, Sydney Blue Gum, Ash, Tasi Oak, Merbau, White Oak, red Ironwood, Kempas,

COLOUR- Browns, Creams, Reds

WIDTH- 134mm to 145mm

HEIGHT--- 14mm (Timber wear level 3.5mm)

COMPOSITE- 3.5mm Timber & 10.5mm Ply- hevea

core

LENGTHS: 11.8200mm

PLY- 10.5mm Australian Hardwood Plywood,

LACQUER- .7 Layers of UV cured lacquer

low-gloss matt & matt brushed finish

ensuring strong joins between boards every time

Simply click your wood planks together with the incredible uniclic multi-fit system. In contrast to most other click profiles, your floor can be installed quickly and easily,



Installation over Heated Subfloors Unlike many other floorcoverings, Quick-Step Timber can be installed over heated concrete subfloors*, providing the following three conditions are met:

- 1. Use 200uM Builders plastic sheeting under the foam underlay prior to installation as per instructions for Installation over Moist Subfloors.
- 2. Ensure that your heating system is run at anticipated operating levels for a period of no less than 2 weeks. The heating system should then be turned off and the subfloor left to cool for three days prior to commencing installation of flooring.
- 3. The maximum surface temperature of the concrete slab should not exceed 28 degrees Celsius at all times.

*It should be noted that, Premium Floors P/L does not recommend the installation of ReadyFlor Spotted Gum, Brushbox, Red Ironwood or Blackbutt in 1 Strip, 2 Strip or 3 Strip, over heated concrete subfloors.

TIP: For best results, installation should be carried out with the heating system turned off. 24 hours after completion of the installation, the heating system should be turned on and the temperature increased gradually over a 7 day period until the normal operating temperature has been reached.



