



# OSMO POLYX OIL

## Information and Maintenance for Timber Floor

Wood that is used indoors for flooring is subjected to wear and tear. Therefore it needs protection that won't impair the natural properties of the wood. Wood must be allowed to "breathe" so that it retains its elasticity and has a positive effect on room climate.

Once Osmo Polyx Oil finish has been applied, the wood retains its natural appearance and feel, the surface will become hard-wearing, non-abrasive, water-repellent, and dirt-resistant. It will be protected against everyday accidents of water, wine, beer, cola, sodas, etc. Should any minor damages occur, surfaces can easily be touched up with no visible brush marks.

Instead of coating the floor with a film, as polyurethane does, these finishes penetrate into wood fibers and protect from within. When the finish wears-as all floor finishes eventually do-spot-repair is so easy that you can keep the finish in good shape indefinitely.

OSMO Polyx-Oil, can be buffed repeatedly to its original luster. Wear spots treated with Osmo Liquid Wax Cleaner buff well too. And when a fresh coat of finish does need to be applied, it's a simple process.

### **Cleaning the Floor As Needed**

- Vacuum, sweep or dust regularly to remove grit. Dust the floor using the Opti-Set with the green Dust-Mop attachment.
- Damp mop as needed using Wash and Care and the Opti-Set with the Micro-mop plush (white fluffy pad) attachment. **Can also use vinegar & water or very mild detergents.**



### **Refreshing/Repairing the Finish As Needed**

- After cleaning the surface thoroughly, allow to dry.
- Apply Liquid Wax Cleaner to refresh high traffic areas. Attach the Active fibre cloth to the Opti-Set and apply a small amount of OSMO Liquid Wax Cleaner to the cloth. Rub this into the surface. Allow to dry for 30 to 60 minutes, until the material dries to a haze. Buff lightly with a soft cotton cloth (you can use either Active fibre cloth or the Micro-mop plush for this light buffing)
- To repair superficial scratches, stains or ground-in dirt, use a white abrasive pad or 000 steel wool to rub a small amount of liquid wax cleaner into the affected area to loosen the dirt and provide a deeper cleaning. Osmo Oil is based on 2 natural waxes (carnauba and candelilla) and 3 natural oils (sunflower, soybean, thistle).

**Enjoy your new floor!**