



Bona
Phone 1300 882 806

Bona Naturale is a new generation of wood floor protection that preserves the look and feel of pure wood without compromising on durability and functionality. The Bona Naturale system offers the same protection as a highly durable waterborne lacquer and is very resistant to wear, chemicals and spills. But best of all it gives the wood a feeling of utmost luxury with the feel of wood underneath your feet. The 2-component version is designed for commercial areas but can also be used to enhance domestic floors.

- Preserves the look and feel of pure wood
- Very high wear resistance
- Can be spot repaired.
- Easy to apply and use
- Classified EC1R for very low emissions
- NMP and NEP free
- VOC 2010 compliant
- Classified R10 (low risk of slipping) according to AS/NZS 486

TECHNICAL DATA

Type of product: 2-component waterborne Naturale topcoat

Solids content: -33%

VOC: max 100 g/litre (incl. hardener)

Sheen (at 60°): -6%

Mixing ratio: 1:10 Naturale Hardener to Naturale Finish

Dilution: Do not dilute

Pot life: 4 hours at 20°C (shorter if warmer)

Drying time, until:
- Ready for sanding: 3-4 hours'
- Light use: 24 hours'
- Full hardness: 7 days'

'Under normal climate conditions. 20°C / 60%RH with reasonable ventilation

Application tools: Bona Roller - White

Application rate: 8-10 m²/litre per coat

Safety Naturale 2-component finish: Unclassified Hardener: Classified (see Safety Data Sheet)

Cleaning: Wipe tools free from residual material before cleaning with a minimum of water. Dried material can be removed with acetone.

Shelf life: 1 year from date of production in unopened original container

Storage/transport: The temperature must not fall below +5°C or exceed +25°C during storage and transport.

Disposal: Wastes and emptied containers should be handled in accordance with local regulations.

Pack size 4.5 litres (incl. Hardener) Ensure the floor is acclimatized to its end-use environment, well sanded, dry and free from sanding dust, oil, wax and other contamination. Prime the surface with Bona Naturale Base prior to use. It is very important that the coverage rate for the primer application is strictly observed, particularly with a 2 coat system, as the Naturale Base provides an important part of the wearing surface and controls the final overall look of the floor.

Allow the finish and hardener to reach room temperature. Insert the filter and shake the container thoroughly before use. Optimal conditions for use are between 18-25°C and 40-60% relative air humidity. High temperatures and low humidity will shorten the drying time whilst low temperatures and high humidity will lengthen the drying time.

Minimum temperature for use is 13°C.

Untreated wood domestic floors, 1 Bona Naturale Base, light sanding, 1 Bona Naturale Finish

Untreated wood commercial floors, 1 Bona Naturale Base, light sanding, 2 Bona Naturale Finish

1. Add 10% hardener to Naturale & immediately shake the mixture thoroughly, for 1 minute. The mixture of Naturale/Hardener should be used directly or at least within 4 hours.
2. Apply Naturale using a Bona Roller - White. Roll with a smooth **flowing** motion alternately across and with the grain of the wood avoiding accumulations of product. Always maintain a 'wet edge' to avoid overlaps. Allow to dry properly before applying **further** coats. Anticipate slightly longer drying time for each coat that is applied.
3. If necessary make an intermediate sanding using a screen or the Bona Scrad System grit P150 (or finer) and remove dust before applying a final coat of finish. **Note:** If the previous coat of finish has been allowed more than 24 hours drying time then an intermediate sanding is always required.

The floor will take light foot traffic approximately 8 hours after the final application. Allow the surface to dry for at least 1 week before covering with carpets or other floor coverings, or loading with heavy objects. Avoid damp mopping the floor during this time.

Clean the floor with Bona Cleaner or with Bona Wood Floor & a microfiber pad. For public areas it may be necessary to introduce a machine based cleaning programme. Worn Naturale surfaces can be renewed by applying a new coat of Naturale after first cleaning and preparing the surface with the Bona Prep System.

Please note: Bona Freshen Up and Wood Floor Refresher cannot be used with Bona Naturale as both the sheen level and slip resistance qualities will be affected. Similarly Bona Naturale should not be maintained with wax polish or similar products.

Please note: Bona Freshen Up and Wood Floor Refresher cannot be used with Bona Naturale as both the sheen level and slip resistance qualities will be affected. Similarly Bona Naturale should not be maintained with wax polish or similar products. The information provided is prepared to the best of our current knowledge & makes no claim to be complete. The User is responsible for establishing that the product and recommendations herein are fit for the designated purpose, wood type and present situation before use. Bona can only guarantee the delivered product. A professional and thereby successful application of the product is beyond our control. If in doubt make a preliminary test. The User is required to read and understand all information contained on package labels and safety data sheets before using this product