



Prestige American White Oak Flooring



**NASH**  
TIMBERS



Rustic American White Oak Flooring

## AMERICAN WHITE OAK

### AMERICAN WHITE OAK.

**COLOUR-** Light brown with pinkish to grey

**WIDTH-** 80mm to 130mm

**LENGTHS** – 0.9 and longer

**GRAIN** – Straight

**GUM VEIN**– Rare

**FIGURE** – Long rays

**TEXTURE-** Medium & Coarse

**HARDNESS (JANKA RATING)-** 6.0

**DURABILITY** – Class 3

**APPLICATION** – Flooring and stair material

**ALL AMERICAN OAK IS TREATED FOR LYCTUS**



AMERICAN WHITE OAK FLOORING

Kiln Dried to Australian averaging MC 10%, (AWO can come in from USA at 6% to 8%) A very important feature as this reduces the timber drying out as it's MC meets Australian Climatic Conditions

**ASK ABOUT OUR UNIQUE**



Species	Visible Gum Vein	Colour Variation	Janka Hardness	Durability	Board Width	Fire Retardant
North Coast Blackbutt	More frequent	Cream to honey brown	9.1	2	80mm to 220mm	Best
Coastal Spotted Gum	Frequent	Light brown to brown	11.0	2	80mm to 210mm	Best
Red Ironbark	Rare	Light Red to red brown	14.0	1	80mm to 180mm	Best
Grey Ironbark	Rare	Pale brown to dark red, variable	14.0	1	80mm to 180mm	Best
Grey Box	Rare	White to light brown(mid brown)	15.0	1	80mm to 180mm	Best
Jarra	Frequent	Rich dark red brown	8.5	2	80mm to 130mm	No
Sydney Blue Gum	More Frequent	Pink to pink brown	9.0	3	80mm to 130mm	No
American White Oak	Never	Light brown with pinkish to grey	6.0	3	80mm to 220mm	Poor
Tallowood	Never	Pale straw to dark brown	8.6	1	60mm to 210mm	N/A
Brushbox	Rare	Pink to brown sapwood present	9.1	3	80mm to 180mm	N/A
Grey Gum	Rare	Red to red brown	1	1	80mm to 180mm	Best
Tasmanian Oak	Frequent	Pale blonde to brown	5.5	4	80 mm to 133mm	Poor

(02) 9337 6800/info@nashtimbers.com.au/nashtimbers.com.au

SHOWROOM → BY APPOINTMENT