

TIMBER FLOOR ADHESIVE

T54J SIKA ADHESIVE



Glue down wooden floor installation with Sika adhesives provides a permanent bond to the sub floor but with a flexible "elastic" floor adhesive rather than a rigid wood floor glue.

SikaBond-T54 is a one-component, no VOC, solvent-free, permanently elastic, strong polyurethane adhesive for full surface bonding of wood flooring. SikaBond-T54 is extremely easy to trowel - preventing arm strain and increasing applicator productivity.

Use Solid and engineered wood flooring (strips, longstrips, planks, panels, boards) mosaic parquet, industrial parquet, wood paving (residential) as well as chipboards can be bonded.

Sikabond T54 features:

- Extremely easy to spread
- Footfall-sound-dampening adhesive
- Suitable for all common types of wood floors
- Suitable for bonding wood floors directly onto old ceramic tiles
- Reduces stress on the substrate: the elastic, material-compatible adhesive reduces transverse stress between the wood floor and the substrate
- Especially for problematic wood such as beech and bamboo
- Suitable for under floor radiant heat installation
- Curing Rate ~ 3.0 mm/24h (+23°C / 50% r.h.)
- Floor may be walked on / sanded 24-48 hours after installation (depending on climatic conditions and adhesive layer thickness)